

QUERY CGIS

The QUERY CGIS command provides information about CGI routines used by the HTTP Daemons.

Syntax: Query CGIs [,PUBLIC=*pubname*] [,SYSlst]

Arguments: PUBLIC= - The specified CGI is displayed. If this parameter is omitted, all CGIs are displayed.

SYSlst - If specified, the results of this request are sent to SYSLSST. If omitted, the results are displayed on the console.

Example:

```
IPN237I query cgis
IPN253I << TCP/IP CGIs >>
IPN432I Public Name:  CGI IPLDT
IPN433I Type:  CGI DLBL:  Driver:  CGI IPLDT
IPN432I Public Name:  CGI IPLD2
IPN433I Type:  CGI-BAL DLBL:  Driver:  IPNFCGIB
IPN432I Public Name:  CGISTATS
IPN433I Type:  CGI DLBL:  Driver:  CGISTATS
IPN432I Public Name:  CGISUBM1
IPN433I Type:  CGI DLBL:  Driver:  CGISUBM1
IPN432I Public Name:  VSECOM
```

Related	DEFINE CGI	- Load a CGI program and make it available for use.
Commands:	DELETE CGI	- Remove a CGI program from storage.
	QUERY PROGRAMS	- Displays the program phases being used by TCP/IP, their characteristics, their memory locations, and the library from which each was loaded.
