QUERY FILES

The QUERY FILES command enables you to inspect the current specification of one or more files in the TCP/IP for VSE file system.

Syntax: `Query FIles [,PUBlic=`*pubname*`] [,SYSlst]`

Arguments: PUBlic= - The public name of a file to be listed. If omitted, all files are listed.

SYSlst   - If specified, the results of this request are sent to SYSLST. If omitted, the results are displayed on the console.

Example:

```
IPN237I query files
IPN253I << TCP/IP Files >>
IPN432I   Public Name: DEVLIB
IPN433I     Type: LIBRARY DLBL: DEVLIB Driver: IPNFLIBR
IPN545I     GID: +0 UID: +0 Permissions: ------
IPN432I   Public Name: IJSYSRS
IPN433I     Type: LIBRARY DLBL: IJSYSRS Driver: IPNFLIBR
IPN545I     GID: +0 UID: +0 Permissions: ------
IPN432I   Public Name: POWER
IPN433I     Type: POWER DLBL:  Driver: IPNFPOWR
IPN545I     GID: +0 UID: +0 Permissions: ------
IPN432I   Public Name: PRD1
IPN433I     Type: LIBRARY DLBL: PRD1 Driver: IPNFLIBR
IPN545I     GID: +0 UID: +0 Permissions: ------
IPN432I   Public Name: PRD2
IPN433I     Type: LIBRARY DLBL: PRD2 Driver: IPNFLIBR
IPN545I     GID: +0 UID: +0 Permissions: ------
IPN432I   Public Name: PRODLIB
IPN433I     Type: LIBRARY DLBL: PRODLIB Driver: IPNFLIBR
IPN545I     GID: +0 UID: +0 Permissions: ------
```

Related Commands:

DEFINE FILE   -   Define a file in the TCP/IP file systems and associate it with a file I/O driver.

DELETE FILE   -   Remove a file from the TCP/IP file system