

QUERY NAMES

The QUERY NAMES command enables you to inspect the contents of the symbolic names table.

Syntax: `Query NAMES [,TYPE={ALL|STATIC|DYNAMIC}] [,SYSlst]`

Arguments:

- TYPE= - May be specified to display a subset of the defined names.
 - STATIC - Only names that were explicitly defined with a DEFINE NAME command will be displayed. This is the default.
 - DYNAMIC - Only those names that were resolved by means of a DNS and are currently in the cache will be displayed.
 - ALL - Both static and dynamic entries will be displayed.

SYSlst - If specified, the results of this request are sent to SYSLSLST. If omitted, the results are displayed on the console.

Example:

```
IPN237I query names
IPN253I << TCP/IP Names >>
IPN503I Symbolic Name: AUTOFTP
IPN504I Script Name: AUTOFTP
IPN503I Symbolic Name: AUTOLPR
IPN504I Script Name: AUTOLPR
IPN503I Symbolic Name: DEVPUNE
IPN504I Script Name: DEVPUNE
IPN503I Symbolic Name: DEVPUN
IPN504I Script Name: DEVPUN
IPN503I Symbolic Name: DEVLST
IPN504I Script Name: DEVLST
IPN503I Symbolic Name: DELL
IPN504I IP Address: 192.168.1.66
IPN503I Symbolic Name: VSE01
IPN504I IP Address: 192.168.1.162
IPN503I Symbolic Name: VSE26
IPN504I IP Address: 192.168.1.161
IPN503I Symbolic Name: VSE
IPN504I IP Address: 192.168.1.161
```

Related Commands: DEFINE NAME - Associate a TCP/IP name with an IP address or a script file.
DELETE NAME - Remove a TCP/IP symbolic name.
