

QUERY OPTIONS

The QUERY OPTIONS command lists the current setting of all variables accessible by the SET command.

Syntax: Query OPTions [,SYSlst]

Arguments: SYSlst - If specified, the results of this request are sent to SYSLST. If omitted, the results are displayed on the console.

Example:

```
IPN237I query options
IPN253I << TCP/IP Current Options >>
IPN452I System ID: 00
IPN453I IP Address: 192.168.1.161 Submask: 255.255.255.0
IPN454I Link Retry Time: 1800
IPN458I Console Hold: On Record: Off
IPN459I Gateway: Off Isolation: Off
IPN804I Telnet translation will use System Default
IPN806I Checksum: Software Connect_Sequence: Off
IPN806I Downcheck: Off Dynamic_Route: On
IPN806I Fixed_Retransmit: Off Full_CETI: On
IPN806I Full_Critical: Off Local_DLBL: On
IPN806I Ping_Message: On
IPN806I Email_Separator_Pages: Off
IPN806I HTTP_Separator_Pages: Off
IPN806I LPR_Separator_Pages: Off
IPN806I FTP_Separator_Pages: Off
IPN806I SDOpen_Extra: Off Spincheck: On
IPN806I Traffic: On Singledest: On
IPN806I ARPdelete: Off ARP_Time: 90000
IPN806I Auto_time: 1500 Pulse_Time: 18000
IPN806I Console_Port: 0
IPN806I DNS1: 65.24.7.3 Timeout: 1200
IPN806I DNS3: 65.24.7.6 Timeout: 1200
IPN806I Reuse_Size: 10
IPN806I Window_Depth: 5
IPN806I Default_Domain:
IPN806I Separator Page Count: 0
IPN806I FTPBATCH_Fetch: Off
IPN806I Subtask_OPEN: Off Stealth mode: Off
IPN806I Memory_Verification: Off
IPN806I Buffer Validation: Off POWERUSERID: SYSTCPIP
IPN806I ListIDCAMS: On AutoLoad: On
```