

QUERY TELNETDS

The QUERY TELNETDS command displays the currently defined Telnet Daemons.

Syntax: Query TELnetds [,ID=*name*] [,SYSLst]

Arguments: ID= - The ID from the DEFINE TELNETD command that created the daemon that you wish to display. If omitted, all Telnet Daemons are displayed.

SYSLst - If specified, the results of this request are sent to SYSLST. If omitted, the results are displayed on the console.

Example:

```
IPN237I query telnetds,id=cf42
IPN469I << TCP/IP TELNET Daemons >>
IPN470I ID: CF42
IPN471I Terminal: TELNLU42 Target: PRODCICS
IPN472I Port: 1042 Driver: TELNETD
IPN473I Menu:
IPN549I Logmode2: S3270 Logmode3: D4B32783
IPN356I Logmode4: D4B32784 Logmode5: D4B32785
IPN350I Current Status: Inactive

IPN237I query telnetds,id=lu05
IPN469I << TCP/IP TELNET Daemons >>
IPN470I ID: LU05
IPN471I Terminal: TELNLG05 Target: DBDCCICS
IPN472I Port: 23 Driver: TELNETD
IPN473I Menu:
IPN549I Logmode2: S3270 Logmode3: D4B32783
IPN356I Logmode4: D4B32784 Logmode5: D4B32785
IPN350I Current Status: Active
IPN351I Current IPaddr: 192.168.0.2
IPN352I Current Applid: DBDCCICS
IPN354I Current Logmod: S3270
```

Related	DEFINE TELNETD	- Create a TN3270 or TN3270E Daemon
Commands:	DELETE TELNETD	- Terminate a TN3270 or TN3270E Daemon
